



Style 1015 - APPLIANCE WIRING MATERIAL

APPLIANCE WIRING MATERIAL

Subj.758
Section 1
Page 1015

Issued: 1959-05-01
Revised: 2013-02-22

Style 1015 Single conductor with extruded insulation

RATING 80, 90 or 105 deg C, 600 Vac or 750 Vdc, Horizontal flame. Optional - 60 or 80 deg C Oil.

CONDUCTOR 30 AWG - 2000 kcmil, Solid or Stranded.

INSULATION Extruded PVC

Conductor size	Minimum average thickness	Minimum thickness at any point
30-9 AWG	30 mils	27 mils
8-7 AWG	45 mils	40 mils
6-2 AWG	60 mils	54 mils
1-4/0 AWG	80 mils	72 mils
250-500 kcmil	95 mils	86 mils
550-1000 kcmil	110 mils	99 mils
1100-2000 kcmil	125 mils	112 mils

STANDARD Appliance Wiring Material UL 758.

MARKING General

USE

Internal Wiring of Appliances. Tags may also indicate the following: 2,500 V peak - for electronic use only.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"