



Style 10553 - APPLIANCE WIRING MATERIAL

APPLIANCE WIRING MATERIAL

Subj. 758
Section 1
Page 10553

Issued: 2001-05-17
Revised: 2019-11-07

Style 10553 Single Conductor Cable using non-integral jacket

RATING 80 deg C, 600 or 1000 Vac, Cable flame.

INSULATION Labeled of complying with Manufacturer's AWM Procedure.

SHIELD Optional.

COVERING Optional. A barrier layer if employed, may be a fibrous wrap, serving or braid; Paper; Nylon: oriented Polyethylene terephthalate; or a thermoplastic tape wrap.

JACKET PUR

dia in inches

1.000 or less	45 mils min average	36 mils minimum at any point
1.001-1.500 dia	60 avg	48 min
1.501-2.500 dia	80 avg	64 min
2.501-4.000 dia	110 avg	88 min.

STANDARD Appliance Wiring Material UL 758.

MARKING

General.

USEInternal or external interconnection of electronic equipment.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"