



# Style 21198 - APPLIANCE WIRING MATERIAL

## APPLIANCE WIRING MATERIAL

Subj.758  
Section 2  
Page 21198

Issued: 2002-02-01  
Revised: 2011-08-29

Style 21198                      Multiple-conductor cable using non-integral jacket.

---

**RATING**                      80 deg C, 300 Vac, Horizontal flame.

---

**CONDUCTOR**                32 AWG minimum, solid or stranded.

---

**INSULATION**              Labeled or complying with Manufacturer's AWM Procedure.

---

**ASSEMBLY**                Consists of two or more conductors, twisted pairs or groups of twisted conductors twisted together. The conductors or groups of conductors may be laid parallel forming a flat, oval or round cable. The lay of the conductor is not specified. A barrier layer and/or fillers are optional. Manufacturer shall maintain a complete description of each assembly. May use same or mixed AWG size.

---

**SHIELD**                      Optional.

---

**COVERING**                Optional. A 6 mils or heavier covering may be extruded over the conductor assembly.

---

**JACKET**                      Extruded TPU, 30 mils minimum average, 24 mils minimum at any point.

---

**STANDARD** Appliance Wiring Material UL 758.

---

**MARKING** General.

---

**USE** Internal wiring of electronic equipment and appliances. Tags may indicate the following: "600 volts Peak for Electronic use only."

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"